DOE/CRN MICROTURBINE EVALUATION PROGRAM

Edward A. Torrero
Cooperative Research Network
National Rural Electric Cooperative Association
Arlington, VA

ELECTRIC COOPERATIVES

- 1000 co-ops in 47 states
- 10% power supply, 30 GW
- 45% distribution lines, 75% land mass
- 13 million service connections, 30 million customers
- 60% residential, 35% commercial/industrial

NRECA

690 Employees at NRECA Supporting 60,000 Co-op Employees

- Legislative, Policy & Communications
- Retirement, Health & Dental Insurance
- Homestead Mutual Funds
- Education/Training to >20,000 registrants
- Technical & Safety Programs
- International Program in 15 Countries Bringing Electricity to 30 Million Customers
- CRN \$3 Million/Year for New Projects

TYPICAL MICROTURBINE USES

Location	Owner	Uses	
Utility facilities	Utility	Grid Peaking Support	
		Baseload Capacity Enhancement	
Customer Sites Utility*		Grid Peaking Support	
		Grid Outage Backup for Customer	
	Customer*	Baseload	
		Demand Reduction by Customer	
		Grid-Dispatched Peaking Support	
		Grid Outage Backup by Customer	

^{*}May include thermal recovery to increase energy efficiency

PROGRAM OBJECTIVES

- Collect test and operation information on installation and performance by NRECA participants
- Identify developmental needs re: permitting, interconnection and building code compliance
- Identify developmental needs re: technology, maintenance and operation
- Provide technology baseline to benchmark future improvements

PARTICIPATING CO-OPS



SITES BEING CONSIDERED

- Office/Warehouse
- Hospital
- Hotels & Motels
- Power Plants
- Nursing Homes
- Colleges & Schools
- Fast-food & Convenience Stores
- Mining Operations
- Manufacturing Plants
- Remote Village Settings

PROGRAM FUNDING & EXPENSES

FUNDING

EXPENSES

•	EPRI/CRN	\$400,000	•	Installation, incl.	
•	CRN	100,000		equipment	\$725,000
•	CO-OPS	650,000	•	12-mo. Optn.	515,000
•	DOE	200,000	•	Overheads	110,000

Total = \$1,350,000

MICROTURBINES

^	Number/Model	Installation	
Two	75 kW Allied-Signal/Honeywell	2000-2001	
Five	28 kW Capstone	2000	
Three 45+ kW Elliott/GE		2000-2001	
One	70 kW NREC Ingersoll-Rand	2001	


REQUIRED ATTRIBUTES

- Recuperator to recycle exhaust heat
- Compressor for natural gas
- Grid parallel with dispatch control
- Grid independent with black start for customer backup
- Fuel options: natural gas, propane and fuel oil
- Thermal recovery


DEMONSTRATION FEATURES

- Low pressure natural gas
- Fuel oil
- Grid-independent operation
- Thermal recovery
- Simulation of remote grid dispatch
- Simulation of SCADA integration/interconnection


ASSESSMENT: LIKELY MKTS FOR CUSTOMER-OWNED UNITS




LIKELY LOCATIONS FOR CO-OP-OWNED MICROTURBINES



ANTICIPATED OPERATING PATTERNS FOR UNITS AT CUSTOMER SITE



ASSESSED VALUE OF OPERATING PATTERNS TO CO-OP OR GRID



POTENTIAL MICROTURBINE GOALS

Target Threshold Values for Enhanced Applicability

Fuel/Maintenance

- 3.6 ¢/kWh Customer Baseload
- 6.1 ¢/kWh Customer Load Management
- 5.7 ¢/kWh Co-op Peaking at customer site

Installed Costs

- \$420 per kW installed cost
- No backup or standby charge for customer installation

Applicable natural gas pricing was assessed to range at \$2.50 to \$4.50 per million BTU or thousand cubic feet.

CO-OP MICROTURBINE WISH LIST

- Demonstrated reliability
- Maintenance track record
- Increased kW output
- Reduced capital costs
- Improved efficiencies
- Improved enclosures for cold weather regions
- Standardized heat exchangers
- Reduced use of external transformers

PROGRAM TASKS

- Characterize Site Applications
- Develop Test/Instrumentation Plan
- Document Installation
- Document Performance and Field Experience
- Complete Final Report

PROGRAM DELIVERABLES

- 3 Test & Instrumentation Plan
- 3 Site Characterization Reports
- ! Commissioning Test Reports
- ! Completion of 8,000 hours of Staged Tests
- ! Final Report